

# NTS-41

## 6" PAR38 Reflector

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

### FEATURES

**Trim:** Precision spun 0.050 aluminum high grade reflector. Separate trim ring available in plastic or metal, may also be used with custom combination of ring finishes.

**Mounting:** Trim includes two coil springs that clip and securely hold the trim into the housing when installed.

### COMPATIBLE HOUSINGS

Compatible with line voltage housings. See individual specification sheets for more information.

### LAMP

100W PAR38 Maximum ([NHIC-170AT](#); [NHIC-17/100DWQA](#))

150W PAR38 Maximum ([NH-260](#); [NHR-260](#))

### LABELS AND LISTINGS


cULus Listed for Damp Locations when used with compatible housings.



### PRODUCT IMAGES AND DIMENSIONS




**NTS-41**



**NTS-41C**



**NTS-41HZ**



### 6" PAR38 Reflector

Catalog No.

- NTS-41** = Specular Clear Reflector with White Plastic Ring
- NTS-41C** = Specular Clear Reflector with Chrome Plastic Ring
- NTS-41HZ** = Haze Reflector with White Plastic Ring

### Compatible Housings

Catalog No.

- NH-260** = Non-IC New Construction / 150W max
- NHR-260** = Non-IC Remodel / 150W max
- NHIC-17/100DWQA** = IC Air-Tight Double Wall New Construction / 100W max
- NHIC-170AT** = IC Air-Tight New Construction / 100W max

Example: **NTS-41C** = Specular Clear Reflector with Chrome Plastic Ring